

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. – 18. (Canceled)

19. (New) A method for providing seamless fail-over of communication between a client computer and a cluster of servers, wherein the cluster of servers includes a first server and a second server and wherein the client computer includes a client application and a network access module by which the client application communicates, the method comprising:

detecting a failure of a first connection with the first server; wherein the first server maps to a server name;

sending a request to the cluster of servers, wherein the request includes the server name;

receiving a response from the second server, wherein the response includes a network address of the second server; and

establishing a second connection with the second server by way of the network address of the second server, wherein the first and second connection are over a Virtual Interface Architecture (VIA) protocol and wherein the detecting, the sending, the receiving, and the establishing occur at the network access module, transparent to the client application.

20. (New) The method of claim 19, further comprising caching the response from the second server in a cache connected to the network access module.

21. (New) The method of claim 20, wherein the establishing the second connection comprises retrieving the network address of the second server from the cache.

22. (New) The method of claim 21, further comprising verifying that the second server maps to the server name.

23. (New) The method of claim 22, wherein verifying that the second server maps to the server name comprises verifying that the second server is responsive to the server name.

24. (New) The method of claim 20, further comprising purging the cache prior to caching the response from the second server.
25. (New) The method of claim 19, wherein the request is sent by User Datagram Protocol (UDP).
26. (New) The method of claim 19, wherein the first server and second server store and retrieve relational data by way of Structured Query Language (SQL) commands.
27. (New) The method of claim 19, wherein the first server is designated as active and the second server is designated as passive.
28. (New) The method of claim 27, wherein the second server periodically sends a keep-alive message to the first server.
29. (New) The method of claim 28, wherein the second server assumes designation as active when the first server fails to response to the keep-alive message.
30. (New) The method of claim 19, wherein the response contains a plurality of port numbers, wherein each port number corresponded to a different communications protocol.
31. (New) The method of claim 19, wherein the first connection and the second connection comprise VIA formatted packets.
32. (New) A computer readable storage medium, for providing seamless fail-over of communication between a client computer and a cluster of servers, wherein the cluster of servers includes a first server and a second server and wherein the client computer includes a client application and a network access module by which the client application communicates, the computer readable storage medium including computer executable instructions to perform the method comprising:
- detecting a failure of a first connection with the first server; wherein the first server maps to a server name;

sending a request to the cluster of servers, wherein the request includes the server name;

receiving a response from the second server, wherein the response includes a network address of the second server; and

establishing a second connection with the second server by way of the network address of the second server, wherein the first and second connection are over a Virtual Interface Architecture (VIA) protocol and wherein the detecting, the sending, the receiving, and the establishing occur at the network access module, transparent to the client application.

33. (New) The computer readable storage medium of claim 32, further comprising computer executable instructions to perform the step of caching the response from the second server in a cache connected to the network access module.

34. (New) The computer readable storage medium of claim 32, wherein the first connection and the second connection comprise VIA formatted packets.

35. (New) A system for providing seamless fail-over of communication with a cluster of servers, wherein the cluster of servers includes a first server and a second server, the system comprising:

a client application; and

a network access module by which the client application communicates; wherein the network access module detects a failure of a first connection with the first server, wherein the first server maps to a server name; sends a request to the cluster of servers, wherein the request includes the server name; receives a response from the second server, wherein the response includes a network address of the second server; and establishes a second connection with the second server by way of the network address of the second server, wherein the first and second connection are over a Virtual Interface Architecture (VIA) protocol and wherein the network access module detects, sends, receives, and establishes transparent to the client application.

DOCKET NO.: MSFT-0688/180597.1
Application No.: 09/924,731
Office Action Dated: December 26, 2007

**PATENT
REPLY FILED UNDER EXPEDITED
PROCEDURE PURSUANT TO
37 CFR § 1.116**

36. (New) The system of claim 35, further comprising a cache connected to the network access module, wherein the network access module caches the response from the second server in the cache.

37. (New) The system of claim 35, wherein the first connection and the second connection comprise VIA formatted packets.